



FloPlast

building the future

SOIL MANIFOLD SOIL & WASTE SYSTEM

FloPlast's Soil Manifold is designed to overcome the requirements of the Building Regulations to help prevent cross flow from opposing inlets, and reduce the risk of siphonage within the system. This can cause gurgling and drain odours as the water in the basin or bath traps can be drawn out when flushing a WC in the main system.

- The Soil Manifold is designed to be installed in a soil stack in the corner of a room.
- The product has a 110mm spigot for connection and a 110mm socket, which will accommodate most UK 110mm soil systems manufactured to BS EN 1329-1 or BS EN 1453-1.
- The fitting is supplied with one open and three closed inlets, which will accommodate 32mm, 40mm and 50mm pipes without the need of boss pipes or soil adaptors.
- To fit 32mm and 40mm pipes, simply push the pipe into the open outlet, if more than one inlet is required, remove the plug and push in the waste pipe or plain ended fitting.
- When connecting 50mm pipe, trim the seal to the marked line and push in the waste pipe or plain ended fitting.
- Ideal for connecting multiple waste and sanitary appliances into one soil pipe.
- Kitemarked to BS EN 1329-1 (KM 544331).

Product	Colour	Code
Soil Manifold (32/40/50mm Connections)		



One open boss

B **G**

SP588

Dimensions (mm)	
A	268
B	210
C	102
D	149
E	132
F	85
G	110Ø
H	89
I	75

