

FloPlast

21.5mm Overflow Waste

A 21.5mm solvent weld overflow system in PVC - U with an extensive range of fittings to meet most installation requirements. Available in White (RAL9003) and Black (RAL9005)



Fixing Guide:

- Fix pipe brackets at maximum 0.5m centres for both vertical and horizontal runs.
- No expansion gap required
- Solvent weld joints to be welded with FloPlast Solvent Cement.

Working Temperatures:

The FloPlast Overflow Waste System may be used to carry liquids when subjected to a continuous flow, with a maximum temperature of 76° c.

Intermittent discharges of up to 100°c may occur, provided that a duration of less than two minutes is observed.

21.5mm Overflow Waste

21.5 mm Overflow Waste Systems

Product	Code	Colour	Qty
3m Overflow Pipe			
	OS01	B W	10
Straight Coupling			
	OS10	B W	100
90° Bend			
	OS11	B W	100
135° (45°) Bend			
	OS12	B W	100
Tee			
	OS13	B W	100
Straight Tank Connector			
	OS14	B W	25
Thread size is 3/4" BSP			
Bent Tank Connector			
	OS15	B W	25
Thread size is 3/4" BSP			
Pipe Clip			
	OS16	B W	100
Overflow Waste Reducer			
	32mm	OS17	B W 10
	40mm	OS18	B W 10

System Features



Overflow waste reducer (32mm & 40mm) will connect to both solvent weld and push fit waste sockets.



Components have a consistent high gloss finish and colour and are essentially maintenance free.



Tough and durable material, yet lightweight for ease of installation